

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 7/27/2022 Version: 1.0

SECTION 1: Identification			
1.1. Identification			
Product form	: Mixture		
Product code	: 9745HOT		
1.2. Recommended use and restrictions on	use		
No additional information available			
1.3. Supplier			
KARCHER NORTH AMERICA 6398 N Karcher Way Aurora, 80019 United States T 303-738-2400 info@karcherna.com			
1.4. Emergency telephone number			
Emergency number	Within USA a	Emergency C nd Canada: 1- and Canada:	all INFOTRAC 24hr/day 7days/week 800-535-5053 011-1-352-323-3500
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance or mixt	ure		
GHS US classification			
Corrosive to metals Category 1 Skin corrosion/irritation Category 1 Serious eye damage/eye irritation Category 1 Specific target organ toxicity (single exposure) Category Full text of H statements : see section 16	gory 3	H290 H314 H318 H335	May be corrosive to metals Causes severe skin burns and eye damage Causes serious eye damage May cause respiratory irritation
2.2. GHS Label elements, including precaut	tionary stateme	ents	
GHS US labeling			
Hazard pictograms (GHS US)			

Signal word (GHS US) Hazard statements (GHS US)

Precautionary statements (GHS US)

- : Danger
- : H290 May be corrosive to metals
 - H314 Causes severe skin burns and eye damage
 - H318 Causes serious eye damage
 - H335 May cause respiratory irritation
- : P234 Keep only in original container.
 - P260 Do not breathe dust, fume, gas, mist, spray, vapors.
 - P261 Avoid breathing dust, fume, gas, mist, spray, vapors.
 - P264 Wash hands, forearms and face thoroughly after handling.
 - P271 Use only outdoors or in a well-ventilated area.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P280 - Wear protective gloves, protective clothing, eye protection, face protection.
	P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
	P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse
	skin with water/shower
	P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
	P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing
	P310 - Immediately call a POISON CENTER, a doctor
	P312 - Call a POISON CENTER, a doctor if you feel unwell
	P363 - Wash contaminated clothing before reuse.
	P390 - Absorb spillage to prevent material-damage.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
	P405 - Store locked up.
	P406 - Store in corrosive resistant container with a resistant inner liner.
	P501 - Dispose of contents/container to hazardous or special waste collection point, in
	accordance with local, regional, national and/or international regulation
2.3. Other hazards which do not	result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

2.

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
SODIUM METASILICATE	CAS-No.: 6834-92-0	30 – 50
PHOSPHORIC ACID, TRISODIUM SALT, DODECAHYDRATE	CAS-No.: 10101-89-0	20 – 30
SODIUM CARBONATE	CAS-No.: 497-19-8	5 – 10
ALCOHOLS, C6-C12, ETHOXYLATED	CAS-No.: 68439-45-2	1 – 5
BUTHOXYETHANOL	CAS-No.: 111-76-2	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

Treat symptomatically.

SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	j media
Suitable extinguishing media	: Water spray. Dry powder. Foam.
5.2. Specific hazards arising from the chem	lical
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Heating increases the fire hazard. No direct explosion hazard. Toxic fumes may be released.
5.3. Special protective equipment and prec	autions for fire-fighters
Firefighting instructions Protection during firefighting	 Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release r	neasures
6.1. Personal precautions, protective	e equipment and emergency procedures
General measures	: Do not handle until all safety precautions have been read and understood.
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapors.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for contai	nment and cleaning up
For containment Methods for cleaning up Other information	 Absorb spilled material with sand or earth. Mechanically recover the product. Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections For further information refer to section 13.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, M	arch 20, 2012 / Rules and Regulations
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling Hygiene measures	 Not expected to present a significant hazard under anticipated conditions of normal use. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapors. Wear personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	any incompatibilities
Technical measures Storage conditions	 Comply with applicable regulations. Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Incompatible materials	: Metals.
SECTION 8: Exposure controls/person	al protection
8.1. Control parameters	
FLOOR WASH	
No additional information available	
SODIUM CARBONATE (497-19-8)	
No additional information available	
SODIUM METASILICATE (6834-92-0)	
No additional information available	
ALCOHOLS, C6-C12, ETHOXYLATED (6843	39-45-2)
No additional information available	
BUTHOXYETHANOL (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) [1]	240 mg/m ³
OSHA PEL (TWA) [2]	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PHOSPHORIC ACID, TRISODIUM SALT, DODECAHYDRATE (10101-89-0)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls Ensure good ventilation of the work station.Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on	basic physica	I and chemical	properties

Physical state	: Solid
Appearance	: Powder.
Color	: Orange
Odor	: lemon-like
Odor threshold	: No data available
рН	: No data available
pH solution	: 11.92 @ 1% SOLUTION
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive properties Oxidizing properties	No data availableNo data available	
9.2 Other information		

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (dermal) :	Not classified Not classified Not classified
SODIUM CARBONATE (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (16 CFR 1500. 40, 24 h, Rabbit, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	2.3 mg/l (2 h, Rat, Male, Experimental value, Inhalation (aerosol))
ATE US (oral)	2800 mg/kg body weight
ATE US (vapors)	2.3 mg/l/4h
ATE US (dust, mist)	2.3 mg/l/4h
SODIUM METASILICATE (6834-92-0)	
LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM METASILICATE (6834-92-0)		
ATE US (oral)	1152 mg/kg body weight	
ALCOHOLS, C6-C12, ETHOXYLATED (68439-4	45-2)	
LD50 oral rat	> 1000 mg/kg (Rat, Oral)	
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)	
BUTHOXYETHANOL (111-76-2)		
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))	
LC50 inhalation rat (mg/l)	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))	
ATE US (oral)	1414 mg/kg body weight	
ATE US (dermal)	1100 mg/kg body weight	
ATE US (gases)	4500 ppmV/4h	
ATE US (vapors)	11 mg/l/4h	
ATE US (dust, mist)	1.5 mg/l/4h	
Skin corrosion/irritation :	Causes severe skin burns.	
· · ·	Causes serious eye damage.	
Respiratory or skin sensitization :	Not classified	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified	
BUTHOXYETHANOL (111-76-2)		
IARC group	3 - Not classifiable	
Reproductive toxicity :	Not classified	
STOT-single exposure :	May cause respiratory irritation.	
SODIUM METASILICATE (6834-92-0)		
STOT-single exposure	May cause respiratory irritation.	
BUTHOXYETHANOL (111-76-2)		
STOT-single exposure	May cause respiratory irritation.	
PHOSPHORIC ACID, TRISODIUM SALT, DODE	ECAHYDRATE (10101-89-0)	
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure :	Not classified	
SODIUM METASILICATE (6834-92-0)		
NOAEL (oral,rat,90 days)	227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)	
BUTHOXYETHANOL (111-76-2)	BUTHOXYETHANOL (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)	
Aspiration hazard :	Not classified	
Viscosity, kinematic :	Not applicable	
	May cause respiratory irritation.	
Symptoms/effects after skin contact :	Burns.	
	Serious damage to eyes.	
Symptoms/effects after ingestion :	Burns.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general :	Before neutralisation, the product may represent a danger to aquatic organisms.
SODIUM CARBONATE (497-19-8)	
LC50 - Fish [1]	300 mg/l (96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	200 – 227 mg/l (48 h, Ceriodaphnia sp., Semi-static system, Fresh water, Experimental value, Locomotor effect)
SODIUM METASILICATE (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
BUTHOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

12.2. Persistence and degradability

SODIUM CARBONATE (497-19-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
SODIUM METASILICATE (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)	
Persistence and degradability	Readily biodegradable in water.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)		
Persistence and degradability	Readily biodegradable in water.	
12.3. Bioaccumulative potential	12.3. Bioaccumulative potential	
SODIUM CARBONATE (497-19-8)		
Partition coefficient n-octanol/water (Log Pow)	-6.19 (Estimated value)	
Bioaccumulative potential	Not bioaccumulative.	
SODIUM METASILICATE (6834-92-0)		
Bioaccumulative potential	Bioaccumulation: not applicable.	
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)		
Partition coefficient n-octanol/water (Log Pow)	3.01 (Estimated value)	
Bioaccumulative potential	Not bioaccumulative.	
BUTHOXYETHANOL (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
12.4. Mobility in soil		
SODIUM CARBONATE (497-19-8)		
Ecology - soil	Low potential for adsorption in soil.	
SODIUM METASILICATE (6834-92-0)		
Surface tension	No data available in the literature	
Ecology - soil	No (test)data on mobility of the substance available.	
BUTHOXYETHANOL (111-76-2)		
Surface tension	65.03 mN/m (20 °C, 2 g/l)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	

12.5. Other adverse effects

Ecology - soil

No additional information available

SECTION 13: Disposal conside	erations
13.1. Disposal methods	
Regional legislation (waste) Waste treatment methods	Disposal must be done according to official regulations.Dispose of contents/container in accordance with licensed collector's sorting instructions.

Highly mobile in soil.

SECTION 14: Transport information	
14.1. UN number	
DOT NA No	: UN1759

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name		
Proper Shipping Name (DOT)	: Corrosive solids, n.o.s., (SODIUM MET,	ASILICATE), 8, III
14.3. Transport hazard class(es)		
• • • • • • •	8 8 CORROSIVE	
14.4. Packing group		
Packing group (DOT)	: III	
14.5. Environmental hazards		
Other information	: No supplementary information available	
14.6. Special precautions for user		
DOT UN-No.(DOT)	: UN1759	
14.7. Transport in bulk according to Annex I	of MARPOL 73/78 and the IBC Cod	le
Not applicable		
SECTION 15: Regulatory information		
15.1. US Federal regulations		
All components of this product are listed, or excluded (TSCA) inventory except for:	from listing, on the United States Environ	mental Protection Agency Toxic Substances Control Act
PHOSPHORIC ACID, TRISODIUM SALT, DODECAHYDRATE	CAS-No. 10101-89-0	20 – 30%

PHOSPHORIC ACID, TRISODIUM SALT, DODECAHYDRATE (10101-89-0)	
CERCLA RQ	5000 lb
15.2. International regulations	

No additional information available

15.3. US State regulations

This product can expose you to ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phra	ises	
H290	May be corrosive to metals	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	
NFPA health hazard NFPA fire hazard NFPA reactivity	 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. 1 - Materials that must be preheated before ignition can occur. 0 - Material that in themselves are normally stable, even under fire conditions. 	
Hazard Rating Health Flammability Physical Personal protection	 2 Moderate Hazard - Temporary or minor injury may occur 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB) 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives. B - Safety glasses, Gloves 	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.