

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 8/23/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product code : 9713HOT

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

KARCHER NORTH AMERICA 6398 N Karcher Way Aurora, 80019 United States T 303-738-2400 info@karcherna.com

1.4. Emergency telephone number

Emergency number : 800-535-5053

For Chemical Emergency Call INFOTRAC 24hr/day 7days/week

Within USA and Canada: 1-800-535-5053 Outside USA and Canada: 011-1-352-323-3500

(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Corrosive to metals Category 1 H290 May be corrosive to metals

Skin corrosion/irritation Category 1 H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity (single exposure) Category 3 H335 May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation P234 - Keep only in original container

Precautionary statements (GHS US) : P234 - Keep only in original container.

P260 - Do not breathe dust, fume, gas, mist, spray, vapors.
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.
P264 - Wash hands, forearms and face thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER, a doctor

P312 - Call a POISON CENTER, a doctor if you feel unwell

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material-damage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
SODIUM METASILICATE	CAS-No.: 6834-92-0	20 – 30
SODIUM CARBONATE	CAS-No.: 497-19-8	10 – 20
ALCOHOLS, C6-C12, ETHOXYLATED	CAS-No.: 68439-45-2	1 – 5
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5
TETRASODIUM EDTA	CAS-No.: 64-02-8	1.517 – 1.599

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

8/23/2022 (Date of issue) EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Fire hazard : Heating increases the fire hazard.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist,

spray, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

8/23/2022 (Date of issue) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling

: Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe

dust, fume, gas, mist, spray, vapors. Wear personal protective equipment.

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Store in corrosive resistant container with a resistant inner liner. Keep only in original container.

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible materials

: Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

NYTRO POWDER ADDITIVE

No additional information available

ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)

No additional information available

SODIUM METASILICATE (6834-92-0)

No additional information available

SODIUM CARBONATE (497-19-8)

No additional information available

SODIUM XYLENE SULFONATE (1300-72-7)

No additional information available

TETRASODIUM EDTA (64-02-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

8/23/2022 (Date of issue) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid Appearance Powder. Color White Odor Mild odour Odor threshold No data available Hq No data available Melting point No data available Freezing point : Not applicable Boiling point : No data available Flash point Not applicable Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) Non flammable. Vapor pressure No data available Relative vapor density at 20 °C No data available Relative density No data available Solubility No data available Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature Not applicable Decomposition temperature : No data available Viscosity, kinematic : Not applicable Viscosity, dynamic : No data available **Explosion limits** Not applicable Explosive properties No data available

9.2. Other information

Oxidizing properties

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Germ cell mutagenicity

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) :	Not classified
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)	
LD50 oral rat	> 1000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
SODIUM METASILICATE (6834-92-0)	
LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1152 mg/kg body weight
SODIUM CARBONATE (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (16 CFR 1500. 40, 24 h, Rabbit, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	2.3 mg/l (2 h, Rat, Male, Experimental value, Inhalation (aerosol))
ATE US (oral)	2800 mg/kg body weight
ATE US (vapors)	2.3 mg/l/4h
ATE US (dust, mist)	2.3 mg/l/4h
SODIUM XYLENE SULFONATE (1300-72-7)	
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))
TETRASODIUM EDTA (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
	Causes severe skin burns. Causes serious eye damage. Not classified
	THE GLOSING THE STATE OF THE ST

8/23/2022 (Date of issue) EN (English US) 6/10

: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

SODIUM METASILICATE (6834-92-0)

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : Not classified

SODIUM METASILICATE (6834-92-0)

NOAEL (oral,rat,90 days)

227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified Viscosity, kinematic : Not applicable

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

LC50 - Fish [1]

EC50 - Daphnia [1]

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

SODIUM METASILICATE (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
SODIUM CARBONATE (497-19-8)	
LC50 - Fish [1]	300 mg/l (96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	200 – 227 mg/l (48 h, Ceriodaphnia sp., Semi-static system, Fresh water, Experimental value, Locomotor effect)
SODIUM XYLENE SULFONATE (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
TETRASODIUM EDTA (64-02-8)	

12.2. Persistence and degradability

ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)	
Persistence and degradability	Readily biodegradable in water.
SODIUM METASILICATE (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)

121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)

625 mg/l (24 h, Daphnia magna, Literature study)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM METASILICATE (6834-92-0)	
ThOD	Not applicable (inorganic)
SODIUM CARBONATE (497-19-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
SODIUM XYLENE SULFONATE (1300-72-7)	
Persistence and degradability	Readily biodegradable in water.
TETRASODIUM EDTA (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 − 0.58 g O₂/g substance

12.3. Bioaccumulative potential

ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)	
Partition coefficient n-octanol/water (Log Pow)	3.01 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.
SODIUM METASILICATE (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.
SODIUM CARBONATE (497-19-8)	
Partition coefficient n-octanol/water (Log Pow)	-6.19 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.
SODIUM XYLENE SULFONATE (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.
TETRASODIUM EDTA (64-02-8)	
Partition coefficient n-octanol/water (Log Pow)	-2.6
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

SODIUM METASILICATE (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.
SODIUM CARBONATE (497-19-8)	
Ecology - soil	Low potential for adsorption in soil.
SODIUM XYLENE SULFONATE (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SODIUM XYLENE SULFONATE (1300-72-7)

Ecology - soil No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1759

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive solids, n.o.s., (SODIUM METASILICATE), 8, III

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



14.4. Packing group

Packing group (DOT) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1759

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

No additional information available

15.3. US State regulations



This product can expose you to ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary

incapacitation or residual injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

NFPA reactivity

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.