

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 6/15/2020 Version: 1.0

### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture
Product code : 1910HOT

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleansing product

### 1.3. Supplier

KARCHER NORTH AMERICA 6398 N Karcher Way Aurora, 80019 United States T 303-738-2400 info@karcherna.com

### 1.4. Emergency telephone number

Emergency number : 800-535-5053

For Chemical Emergency Call INFOTRAC 24hr/day 7days/week

Within USA and Canada: 1-800-535-5053 Outside USA and Canada: 011-1-352-323-3500

(collect calls accepted)

### **SECTION 2: Hazard(s) identification**

#### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation Category 1 H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a poison center or doctor

P321 - Specific treatment (see supplemental first aid instruction on this label)

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
SODIUM METASILICATE	CAS-No.: 6834-92-0	5 – 10
BUTOXYDIGLYCOL	CAS-No.: 112-34-5	1 – 5
LOW FOAM NONIONIC SURFACTANT	CAS-No.: PROPRIETARY	1 – 5
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5

Full text of hazard classes and H-statements: see section 16

### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures after skin contact

First-aid measures general

: Call a poison center/doctor/physician if you feel unwell. First-aid measures after inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Wash immediately with lots of water (15 minutes)/shower. Take victim to a

doctor if irritation persists.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a doctor/medical

service.

First-aid measures after ingestion : If swallowed, seek medical advice immediately and show this container or label. Rinse mouth out with water. Do not induce vomiting. Immediately consult a doctor/medical service.

### 4.2. Most important symptoms and effects (acute and delayed)

: Causes skin irritation. Symptoms/effects after skin contact Symptoms/effects after eye contact : Causes serious eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

6/15/2020 (Date of issue) EN (English US) 2/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Adapt extinguishing media to the environment for surrounding fires.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Non-flammable.

Explosion hazard : No data available on direct explosion hazard.

Reactivity in case of fire : Product is not explosive.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.

Evacuate area. Fight fire with normal precautions from a reasonable distance.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood. Avoid contact with

skin and eyes.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Protective goggles. Protective clothing.

Gloves.

Emergency procedures : Avoid contact with skin and eyes. Consider evacuation. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Protective gloves. Safety

glasses. Self-contained breathing apparatus.

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area. Prevent from

entering sewers, basements and workpits, or any place where its accumulation can be

dangerous.

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Collect spillage. Contain large spillage with sand or

earth. Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Consult an expert

on waste disposal or treatment.

Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. Carefully collect

the spill/leftovers. Clean contaminated surfaces with an excess of water.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

No additional information available

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

6/15/2020 (Date of issue) EN (English US) 3/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Clean contaminated clothing. Do not breathe vapors.

Keep container tightly closed.

Hygiene measures : Observe normal hygiene standards.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Store in a well-ventilated place. Keep container tightly

closed.

Storage conditions : Keep container tightly closed. Store in a well-ventilated place. Keep container tightly closed.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### **SHOP FLOOR CLEANER**

No additional information available

#### **SODIUM METASILICATE (6834-92-0)**

No additional information available

### LOW FOAM NONIONIC SURFACTANT (PROPRIETARY)

No additional information available

#### **BUTOXYDIGLYCOL (112-34-5)**

#### **USA - ACGIH - Occupational Exposure Limits**

Local name	Diethylene glycol monobutyl ether
ACGIH OEL TWA [ppm]	10 ppm (Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Hematologic, liver & kidney eff
Regulatory reference	ACGIH 2019

### **SODIUM XYLENE SULFONATE (1300-72-7)**

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure that there is a suitable ventilation system.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

nanu protection.	Hand	protection:
------------------	------	-------------

Gloves

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Safety glasses

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Liquid. Color : red

Odor : characteristic
Odor threshold : No data available

pH : 13.3

Melting point: No data availableFreezing point: No data availableBoiling point: No data available

Flash point : > 212 °F

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Solubility No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature No data available Decomposition temperature No data available Viscosity, kinematic No data available Viscosity, dynamic No data available **Explosion limits** No data available Explosive properties No data available Oxidizing properties : No data available

#### 9.2. Other information

VOC CONTENT:

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

6/15/2020 (Date of issue) EN (English US) 5/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

No additional information available

## **SECTION 11: Toxicological information**

SECTION 11: Toxicological inform	tion
11.1. Information on toxicological effe	ts
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	<ul><li>: Not classified</li><li>: Not classified</li><li>: Not classified</li></ul>
SODIUM METASILICATE (6834-92-0)	
LD50 oral rat	1152 - 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1152 mg/kg body weight
BUTOXYDIGLYCOL (112-34-5)	
LD50 dermal rabbit	2764 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2410 mg/kg body weight
ATE US (dermal)	2764 mg/kg body weight
SODIUM XYLENE SULFONATE (1300	2-7)
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal 14 day(s))
Skin corrosion/irritation	: Causes severe skin burns. pH: 13.3
Serious eye damage/irritation	: Causes serious eye damage. pH: 13.3
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity STOT-single exposure	: Not classified : Not classified
SODIUM METASILICATE (6834-92-0)	. NOT GROUNDE
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
SODIUM METASILICATE (6834-92-0)	
NOAEL (oral,rat,90 days)	227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 9 Day Oral Toxicity in Rodents)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTOXYDIGLYCOL (112-34-5)	
NOAEL (oral,rat,90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

# SECTION 12: Ecological information

# 12.1. Toxicity

SODIUM METASILICATE (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
BUTOXYDIGLYCOL (112-34-5)	
LC50 - Fish [1]	1300 mg/l (Equivalent or similar to OECD 203, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Daphnia [1]	> 100 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
SODIUM XYLENE SULFONATE (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Daphnia [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

# 12.2. Persistence and degradability

SODIUM METASILICATE (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
BUTOXYDIGLYCOL (112-34-5)	
Persistence and degradability Readily biodegradable in water.	
SODIUM XYLENE SULFONATE (1300-72-7)	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

SODIUM METASILICATE (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTOXYDIGLYCOL (112-34-5)	
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
SODIUM XYLENE SULFONATE (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow) -3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

SODIUM METASILICATE (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.
BUTOXYDIGLYCOL (112-34-5)	
Surface tension	27 mN/m (25 °C, 0.00212 mol/g)
Ecology - soil	Highly mobile in soil.
SODIUM XYLENE SULFONATE (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

No additional information available

### **SECTION 14: Transport information**

#### 14.1. UN number

DOT NA No : UN1760

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (SODIUM METASILICATE), 8, III

6/15/2020 (Date of issue) EN (English US) 8/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



### 14.4. Packing group

Packing group (DOT) : III

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1760

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

SHOP FLOOR CLEANER	
U.S California - Proposition 65 - Carcinogens List	Yes
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
U.S California - Proposition 65 - Other information	ETHYLENE OXIDE (75-21-8)



This product can expose you to ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary

incapacitation or residual injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

NFPA reactivity

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.