



SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 9/22/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product code : 9748HOT

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

KARCHER NORTH AMERICA
6398 N Karcher Way
Aurora, 80019
United States
T 303-738-2400
info@karcherna.com

1.4. Emergency telephone number

Emergency number : 800-535-5053
For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
Within USA and Canada: 1-800-535-5053
Outside USA and Canada: 011-1-352-323-3500
(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H318 - Causes serious eye damage
Precautionary statements (GHS US) : P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
SODIUM CARBONATE	CAS-No.: 497-19-8	30 – 50
C9-C11 ALCOHOLS ETHOXYLATED	CAS-No.: 68439-46-3	5 – 10
BUTHOXYETHANOL	CAS-No.: 111-76-2	1 – 5
TETRASODIUM EDTA	CAS-No.: 64-02-8	0.999 – 1.053

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after eye contact	: Serious damage to eyes.
------------------------------------	---------------------------

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Specific hazards arising from the chemical

Fire hazard	: Heating increases the fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SUPER X

No additional information available

C9-C11 ALCOHOLS ETHOXYLATED (68439-46-3)

No additional information available

BUTHOXYETHANOL (111-76-2)

USA - ACGIH - Occupational Exposure Limits

Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)	
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA [1]	240 mg/m ³
OSHA PEL TWA [2]	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
SODIUM CARBONATE (497-19-8)	
No additional information available	
TETRASODIUM EDTA (64-02-8)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Powder.
Color : light red
Odor : Characteristic odour
Odor threshold : No data available
pH : No data available

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH solution	: 10.98 @ 1% SOLUTION
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1414 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
SODIUM CARBONATE (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (16 CFR 1500. 40, 24 h, Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	2.3 mg/l (2 h, Rat, Male, Experimental value, Inhalation (aerosol))
ATE US (oral)	2800 mg/kg body weight
ATE US (vapors)	2.3 mg/l/4h
ATE US (dust, mist)	2.3 mg/l/4h
TETRASODIUM EDTA (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
BUTHOXYETHANOL (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
BUTHOXYETHANOL (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
BUTHOXYETHANOL (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable
Symptoms/effects after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTHOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

SODIUM CARBONATE (497-19-8)	
LC50 - Fish [1]	300 mg/l (96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	200 – 227 mg/l (48 h, Ceriodaphnia sp., Semi-static system, Fresh water, Experimental value, Locomotor effect)

TETRASODIUM EDTA (64-02-8)	
LC50 - Fish [1]	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 - Crustacea [1]	625 mg/l (24 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

BUTHOXYETHANOL (111-76-2)	
Persistence and degradability	Readily biodegradable in water.

SODIUM CARBONATE (497-19-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

TETRASODIUM EDTA (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O ₂ /g substance

12.3. Bioaccumulative potential

BUTHOXYETHANOL (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SODIUM CARBONATE (497-19-8)	
Partition coefficient n-octanol/water (Log Pow)	-6.19 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

TETRASODIUM EDTA (64-02-8)	
Partition coefficient n-octanol/water (Log Pow)	-2.6

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TETRASODIUM EDTA (64-02-8)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

12.4. Mobility in soil

BUTHOXYETHANOL (111-76-2)

Surface tension	65.03 mN/m (20 °C, 2 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

SODIUM CARBONATE (497-19-8)

Ecology - soil	Low potential for adsorption in soil.
----------------	---------------------------------------

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT
No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SUPER X

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Full text of H-phrases

H318	Causes serious eye damage
------	---------------------------

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.