

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/29/2020 Supersedes: 6/15/2020 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture Product code 1910LAN

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleansing product

1.3. Supplier

KARCHER NORTH AMERICA 6398 N Karcher Way Aurora, 80239 **United States** T 303-738-2400 info@karcher.com

1.4. Emergency telephone number

Emergency number : 800-535-5053

For Chemical Emergency Call INFOTRAC 24hr/day 7days/week

Within USA and Canada: 800-535-5053 Outside USA and Canada: 1-352-323-3500

(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1 H314 Causes severe skin burns and eye damage.

Serious eye damage/eye irritation, Category 1 H318 Causes serious eye damage.

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dusts or mists.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing

protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P363 - Take off immediately all contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
SODIUM METASILICATE	CAS-No.: 6834-92-0	1 – 5
BUTOXYDIGLYCOL	CAS-No.: 112-34-5	1 – 5
LOW FOAM NONIONIC SURFACTANT	CAS-No.: PROPRIETARY	1 – 5
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Wash immediately with lots of water (15 minutes)/shower. Take victim to a

with plenty of water. Wash immediately with lots of water (15 minutes)/shower. Take victim to a doctor if irritation persists.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove contact lenses, if present and easy to do. Continue rinsing. Consult a doctor/medical service

If a very larger of a call to a discalled visa increased in tally and all as

First-aid measures after ingestion : If swallowed, seek medical advice immediately and show this container or label. Rinse mouth out with water. Do not induce vomiting. Immediately consult a doctor/medical service.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

6/29/2020 (Issue date) US - en 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Adapt extinguishing media to the environment for surrounding fires.

5.2. Specific hazards arising from the chemical

Fire hazard : Non-flammable.

Explosion hazard : No data available on direct explosion hazard.

Reactivity in case of fire : Product is not explosive.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.

Evacuate area. Fight fire with normal precautions from a reasonable distance.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Protective goggles. Protective clothing.

Gloves.

Emergency procedures : Avoid contact with skin and eyes. Consider evacuation. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Protective gloves. Safety

glasses. Self-contained breathing apparatus.

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area. Prevent from

entering sewers, basements and workpits, or any place where its accumulation can be

dangerous.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Collect spillage. Contain large spillage with sand or

earth. Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Consult an expert

on waste disposal or treatment.

Methods for cleaning up : Absorb remaining liquid with sai

: Absorb remaining liquid with sand or inert absorbent and remove to safe place. Carefully collect

the spill/leftovers. Clean contaminated surfaces with an excess of water.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

6/29/2020 (Issue date) US - en 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Clean contaminated clothing. Do not breathe vapors.

Keep container tightly closed.

Hygiene measures : Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Store in a well-ventilated place. Keep container tightly

closed

Storage conditions : Keep container tightly closed. Store in a well-ventilated place. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SHOP FLOOR CLEANER

No additional information available

LOW FOAM NONIONIC SURFACTANT PROPRIETARY

No additional information available

BUTOXYDIGLYCOL 112-34-5

No additional information available

USA - ACGIH - Occupational Exposure Limits

Local name	Diethylene glycol monobutyl ether
ACGIH OEL TWA	10 ppm (Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Hematologic, liver & kidney eff
Regulatory reference	ACGIH 2019

SODIUM XYLENE SULFONATE 1300-72-7

No additional information available

SODIUM METASILICATE 6834-92-0

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure that there is a suitable ventilation system.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:	
Gloves	
Eye protection:	
Safety glasses	

6/29/2020 (Issue date) US - en 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: LiquidColor: Red

Odor : characteristic
Odor threshold : No data available

pH : 13.3

Melting point: No data availableFreezing point: No data availableBoiling point: No data available

Flash point : > 212 °F

Relative evaporation rate (butyl acetate=1) : No data available Flammability : No data available : No data available Vapor pressure Relative vapor density at 20°C : No data available Relative density : No data available : No data available Solubility Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

1	ľ	П	Inf	forma	tion	on i	toxico	logical	leffects
	_	•	ш	Ollia	ион	UII	LUXICU	louica	I GIIGUIS

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

BUTOXYDIGLYCOL (112-34-5)	
LD50 dermal rabbit	2764 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2410 mg/kg body weight
ATE US (dermal)	2764 mg/kg body weight

SODIUM XYLENE SULFONATE (1300-72-7)		
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))	
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))	

SODIUM METASILICATE (6834-92-0)	DIUM METASILICATE (6834-92-0)			
LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 7 day(s))			
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))			
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))			
ATE US (oral)	1152 mg/kg body weight			

Skin corrosion/irritation : Causes severe skin burns.

pH: 13.3

Serious eye damage/irritation : Causes serious eye damage.

pH: 13.3

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified

SODIUM METASILICATE (6834-92-0)

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTOXYDIGLYCOL (112-34-5)		
NOAEL (oral,rat,90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)	
SODIUM METASILICATE (6834-92-0)		
NOAEL (oral,rat,90 days)	227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	
Aspiration hazard	: Not classified	
Viscosity, kinematic	: No data available	
Symptoms/effects after skin contact	: Causes skin irritation.	
Symptoms/effects after eye contact	: Causes serious eye irritation.	

SECTION 12: Ecological information

12.1. Toxicity

BUTOXYDIGLYCOL112-34-5		
LC50 - Fish [1]	1300 mg/l (Equivalent or similar to OECD 203, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	> 100 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)	
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)	
SODIUM XYLENE SULFONATE1300-72-7		
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)	
EC50 - Crustacea [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)	
SODIUM METASILICATE6834-92-0		
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)	
EC50 - Crustacea [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	

12.2. Persistence and degradability

BUTOXYDIGLYCOL112-34-5		
Persistence and degradability	Readily biodegradable in water.	
SODIUM XYLENE SULFONATE1300-72-7		
Persistence and degradability	Readily biodegradable in water.	
SODIUM METASILICATE6834-92-0		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	

6/29/2020 (Issue date) US - en 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

BUTOXYDIGLYCOL112-34-5		
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
SODIUM XYLENE SULFONATE1300-72-7		
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential	Not bioaccumulative.	
SODIUM METASILICATE6834-92-0		
Bioaccumulative potential	Bioaccumulation: not applicable.	

12.4. Mobility in soil

BUTOXYDIGLYCOL112-34-5		
Surface tension	27 mN/m (25 °C, 0.00212 mol/g)	
Ecology - soil	Highly mobile in soil.	
SODIUM XYLENE SULFONATE1300-72-7		
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)	
Ecology - soil	No (test)data on mobility of the substance available.	
SODIUM METASILICATE6834-92-0		
Surface tension	No data available in the literature	
Ecology - soil	No (test)data on mobility of the substance available.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

14.1. UN number

UN-No. (DOT) : UN1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8

6/29/2020 (Issue date) US - en 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



14.4. Packing group

Packing group (DOT) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No. (DOT) : UN1760

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used

provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L
CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

No additional information available

6/29/2020 (Issue date) US - en 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary

incapacitation or residual injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

6/29/2020 (Issue date) US - en 10/10