



PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 5/18/2022 Revision date: 7/15/2025 Supersedes: 5/18/2022 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product code : 1992HOT

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleansing product

1.3. Supplier

KARCHER NORTH AMERICA
6398 N Karcher Way
Aurora, 80019
United States
T 303-738-2400
info@karcher.com

1.4. Emergency telephone number

Emergency number : 800-535-5053
For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
Within USA and Canada: 1-800-535-5053
Outside USA and Canada: 011-1-352-323-3500
(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 3	H226	Flammable liquid and vapour.
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Skin corrosion/irritation, Category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P243 - Take action to prevent static discharges.
P260 - Do not breathe dusts or mists.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves, protective clothing, eye and face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P363 - Take off immediately all contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
ALCOHOLS, C6-C12, ETHOXYLATED	CAS-No.: 68439-45-2	30 – 50
BUTOXYDIGLYCOL Component	CAS-No.: 112-34-5	20 – 30
1-BUTANOL	CAS-No.: 71-36-3	0.31 – 1.55

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Harmful if swallowed. Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Heating increases the fire hazard. Flammable liquid and vapour.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PANEL WASH LIQUID ADDITIVE	
No additional information available	
ALCOHOLS, C6-C12, ETHOXYLATED 68439-45-2	
No additional information available	
1-BUTANOL 71-36-3	
No additional information available	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm
BUTOXYDIGLYCOL 112-34-5	
No additional information available	
USA - ACGIH - Occupational Exposure Limits	
Local name	Diethylene glycol monobutyl ether
ACGIH OEL TWA	10 ppm (Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Hematologic, liver & kidney eff
Regulatory reference	ACGIH 2019

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Purple
Odour	: Characteristic odor
Odour threshold	: No data available
pH	: 1.6
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : No data available
Acute toxicity (inhalation) : No data available

PANEL WASH LIQUID ADDITIVE	
ATE US (oral)	1099.203 mg/kg bodyweight
ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2)	
LD50 oral rat	> 1000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
ATE US (oral)	500 mg/kg bodyweight
1-BUTANOL (71-36-3)	
LD50 oral rat	2292 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	3430 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	2292 mg/kg bodyweight
ATE US (dermal)	3430 mg/kg bodyweight
BUTOXYDIGLYCOL (112-34-5)	
LD50 dermal rabbit	2764 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2410 mg/kg bodyweight
ATE US (dermal)	2764 mg/kg bodyweight

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Skin corrosion/irritation	: Causes severe skin burns. pH: 1.6
Serious eye damage/irritation	: Causes serious eye damage. pH: 1.6
Respiratory or skin sensitisation	: No data available
Germ cell mutagenicity	: No data available
Carcinogenicity	: No data available
Reproductive toxicity	: No data available
STOT-single exposure	: No data available

1-BUTANOL (71-36-3)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: No data available

BUTOXYDIGLYCOL (112-34-5)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	: No data available
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Harmful if swallowed. Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

1-BUTANOL71-36-3

LC50 - Fish [1]	1376 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	1328 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	225 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

BUTOXYDIGLYCOL112-34-5

LC50 - Fish [1]	1300 mg/l (Equivalent or similar to OECD 203, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 100 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

ALCOHOLS, C6-C12, ETHOXYLATED68439-45-2

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

1-BUTANOL71-36-3	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.1 – 1.92 g O ₂ /g substance
Chemical oxygen demand (COD)	2.46 g O ₂ /g substance
ThOD	2.59 g O ₂ /g substance
BOD (% of ThOD)	0.33 – 0.79

BUTOXYDIGLYCOL112-34-5	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

ALCOHOLS, C6-C12, ETHOXYLATED68439-45-2	
Partition coefficient n-octanol/water (Log Pow)	3.01 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

1-BUTANOL71-36-3	
BCF - Other aquatic organisms [1]	3.162 l/kg (BCFBAF v3.01, Calculated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

BUTOXYDIGLYCOL112-34-5	
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

1-BUTANOL71-36-3	
Surface tension	69.9 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. May be harmful to plant growth, blooming and fruit formation.

BUTOXYDIGLYCOL112-34-5	
Surface tension	27 mN/m (25 °C, 0.00212 mol/g)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

14.1. UN number

UN-No. (DOT) : UN1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



14.4. Packing group

Packing group (DOT) : I

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No. (DOT) : UN1760
DOT Special Provisions (49 CFR 172.102) : A7 - Steel packagings must be corrosion-resistant or have protection against corrosion. B10 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks, and DOT 57 portable tanks are not authorized. T14 - 6 mm Prohibited 178.275(g)(3). TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: t_r is the maximum mean bulk temperature during transport, t_f is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (t_f) and the maximum mean bulk temperature during transportation (t_r) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d_{15} and d_{50} are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Non Bulk (49 CFR 173.xxx) : 201
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 0.5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 2.5 L

PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1-BUTANOL	CAS-No. 71-36-3	0.31 – 1.55%
-----------	-----------------	--------------

1-BUTANOL71-36-3

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 7/15/2025


Full text of hazard classes and H-statements

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



PANEL WASH LIQUID ADDITIVE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hazard Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

: B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA 2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.