

# Safety Data Sheet

#### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture Product code : 8977LAN

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

KARCHER NORTH AMERICA 6398 N Karcher Way Aurora, 80239 **United States** T 303-738-2400 info@karcher.com

#### 1.4. Emergency telephone number

**Emergency number** : 800-535-5053

For Chemical Emergency Call INFOTRAC 24hr/day 7days/week

Within USA and Canada: 800-535-5053 Outside USA and Canada: 1-352-323-3500

(collect calls accepted)

### SECTION 2: Hazard(s) identification

# 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation, Category 1 H314 Causes severe skin burns and eye damage.

Serious eye damage/eye irritation, Category 1 H318 Causes serious eye damage.

Full text of H-statements: see section 16

### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labelling**

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dusts or mists.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing

protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P363 - Take off immediately all contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

#### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%
TETRASODIUM EDTA	CAS-No.: 64-02-8	19.965 – 21.044
SODIUM XYLENE SULFONATE	CAS-No.: 1300-72-7	5 – 10
SODIUM HYDROXIDE	CAS-No.: 1310-73-2	1 – 5

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician

immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

# 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

# SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard. Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

# 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent

migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 13.

### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

8/12/2025 (Issue date) US - en 3/11

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

: Keep in a cool, well-ventilated place away from heat. Technical measures

Storage conditions : Store locked up.

Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

### **CLEAN WONDER PART A**

No additional information available

#### **TETRASODIUM EDTA 64-02-8**

No additional information available

#### **SODIUM XYLENE SULFONATE 1300-72-7**

No additional information available

#### **SODIUM HYDROXIDE 1310-73-2**

No additional information available

#### **USA - ACGIH - Occupational Exposure Limits**

Local name	Sodium hydroxide
ACGIH OEL C	2 mg/m³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL TWA	2 mg/m³

OSHA Annotated Table Z-1

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

: Avoid release to the environment. Environmental exposure controls

#### 8.3. Individual protection measures/Personal protective equipment

# Personal protective equipment:

Regulatory reference (US-OSHA)

Wear recommended personal protective equipment.

Hand	prote	ction:
------	-------	--------

Protective gloves

#### Eye protection:

Safety glasses

8/12/2025 (Issue date) US - en 4/11

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):







# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.

Colour : Colourless
Odour : Odourless

Odour threshold : No data available

pH : 13.09

Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butylacetate=1) : No data available
Flammability : Not applicable.
Vapour pressure : No data available

Relative vapour density at 20°C No data available Relative density : No data available : 1.21504 g/cm<sup>3</sup> Density Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available No data available Explosive limits Explosive properties No data available Oxidising properties No data available

# 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : No data available
Acute toxicity (dermal) : No data available
Acute toxicity (inhalation) : No data available

LD50 oral rat > 2000 mg/kg (Rat, Oral)

### **SODIUM XYLENE SULFONATE (1300-72-7)**

LD50 oral rat	> 7000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))

Skin corrosion/irritation : Causes severe skin burns.

pH: 13.09

Serious eye damage/irritation : Causes serious eye damage.

pH: 13.09

Respiratory or skin sensitisation : No data available Germ cell mutagenicity : No data available : No data available Carcinogenicity Reproductive toxicity : No data available STOT-single exposure No data available : No data available STOT-repeated exposure : No data available Aspiration hazard Viscosity, kinematic : No data available

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

8/12/2025 (Issue date) US - en 6/11

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

TETRASODIUM EDTA64-02-8	
LC50 - Fish [1]	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 - Crustacea [1]	625 mg/l (24 h, Daphnia magna, Literature study)
SODIUM XYLENE SULFONATE1300-72-7	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
SODIUM HYDROXIDE1310-73-2	
EC50 - Crustacea [1]	40.4 mg/l Test organisms (species): Ceriodaphnia sp.

# 12.2. Persistence and degradability

TETRASODIUM EDTA64-02-8	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.54 − 0.58 g O₂/g substance
SODIUM XYLENE SULFONATE1300-72-7	
Persistence and degradability Readily biodegradable in water.	
SODIUM HYDROXIDE1310-73-2	
Persistence and degradability	Biodegradability: not applicable.

# 12.3. Bioaccumulative potential

TETRASODIUM EDTA64-02-8	
Partition coefficient n-octanol/water (Log Pow)	-2.6
Bioaccumulative potential	Not bioaccumulative.
SODIUM XYLENE SULFONATE1300-72-7	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.
SODIUM HYDROXIDE1310-73-2	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

# 12.4. Mobility in soil

SODIUM XYLENE SULFONATE1300-72-7	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.
SODIUM HYDROXIDE1310-73-2	
Ecology - soil No (test)data on mobility of the component(s) available.	

### 12.5. Other adverse effects

No additional information available

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

# **SECTION 14: Transport information**

### 14.1. UN number

 UN-No. (DOT)
 : UN3266

 UN-No. (TDG)
 : UN3266

 UN-No. (IMDG)
 : 3266

 UN-No. (IATA)
 : 3266

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquid, basic, inorganic, n.o.s.

Proper Shipping Name (TDG) : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. Proper Shipping Name (IMDG) : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

Proper Shipping Name (IATA) : Corrosive liquid, basic, inorganic, n.o.s.

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



### TDG

Transport hazard class(es) (TDG) : 8
Hazard labels (TDG) : 8



#### **IMDG**

Transport hazard class(es) (IMDG) : 8
Danger labels (IMDG) : 8



### IATA

Transport hazard class(es) (IATA) : 8
Danger labels (IATA) : 8

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)



#### 14.4. Packing group

Packing group (DOT) Packing group (TDG) : 1 Packing group (IMDG) : 1 Packing group (IATA) : 1

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

DOT

UN-No. (DOT) : UN3266

DOT Special Provisions (49 CFR 172.102) : T14 - 6 6 mm Prohibited 178.275(g)(3).

> TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59

F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178,275 of this subchapter, where the test pressure is 1.5 times the MAWP.

: 201 DOT Packaging Non Bulk (49 CFR 173.xxx) : 243 DOT Packaging Bulk (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail (49 : 0.5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 2.5 L

CFR 175.75)

**DOT Vessel Stowage Location** : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

: 40 - Stow "clear of living quarters",52 - Stow "separated from" acids **DOT Vessel Stowage Other** 

**TDG** 

UN-No. (TDG) : UN3266

8/12/2025 (Issue date) US - en 9/11

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

**TDG Special Provisions** 

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3).

(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;

(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;

(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or

(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.

ERAP Index : 3000
Explosive Limit and Limited Quantity Index : 0
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger : 0.5 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 154

#### **IMDG**

Special provisions (IMDG): 274Limited quantities (IMDG): 0Excepted quantities (IMDG): E0Packing instructions (IMDG): P001Tank instructions (IMDG): T14Tank special provisions (IMDG): TP2, TP27

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : B

Properties and observations (IMDG) : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

#### **IATA**

PCA Excepted quantities (IATA) : E0 : Forbidden PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) : Forbidden : 850 PCA packing instructions (IATA) : 0.5L PCA max net quantity (IATA) : 854 CAO packing instructions (IATA) CAO max net quantity (IATA) : 2.5L Special provisions (IATA) : A3, A803 ERG code (IATA) : 8L

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

8/12/2025 (Issue date) US - en 10/11

# Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

# **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### **SODIUM HYDROXIDE1310-73-2**

CERCLA RQ 1000 lb

### 15.2. International regulations

#### **CANADA**

#### **TETRASODIUM EDTA64-02-8**

Listed on the Canadian DSL (Domestic Substances List)

#### **SODIUM XYLENE SULFONATE1300-72-7**

Listed on the Canadian DSL (Domestic Substances List)

#### **SODIUM HYDROXIDE1310-73-2**

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

### **TETRASODIUM EDTA64-02-8**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### **SODIUM XYLENE SULFONATE1300-72-7**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

No additional information available

# **SECTION 16: Other information**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements		
H314	Causes severe skin burns and eye damage	
H318 Causes serious eye damage		

Safety Data Sheet (SDS), USA 2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.