



ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 7/6/2021 Revision date: 9/9/2025 Supersedes: 7/6/2021 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product code : 1914HOT

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleansing product

1.3. Supplier

KARCHER NORTH AMERICA
6398 N Karcher Way
Aurora, 80019
United States
T 303-738-2400
info@karcher.com

1.4. Emergency telephone number

Emergency number : 800-535-5053
For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
Within USA and Canada: 1-800-535-5053
Outside USA and Canada: 011-1-352-323-3500
(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

| | | |
|---|------|--|
| Skin corrosion/irritation, Category 1 | H314 | Causes severe skin burns and eye damage. |
| Serious eye damage/eye irritation, Category 1 | H318 | Causes serious eye damage. |

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dusts or mists.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center/doctor.

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P321 - Specific treatment (see supplemental first aid instruction on this label).
P363 - Take off immediately all contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of hazardous or special waste collection point, in accordance with local regulations to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|-------------------------------|---------------------|---------------|
| BUTHOXYETHANOL | CAS-No.: 111-76-2 | 1 – 5 |
| ALCOHOLS, C6-C12, ETHOXYLATED | CAS-No.: 68439-45-2 | 1 – 5 |
| SODIUM METASILICATE | CAS-No.: 6834-92-0 | 1 – 5 |
| TETRASODIUM EDTA | CAS-No.: 64-02-8 | 1.998 – 2.106 |
| SODIUM XYLENE SULFONATE | CAS-No.: 1300-72-7 | 1 – 5 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Burns.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Do not handle until all safety precautions have been read and understood. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.
Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Store locked up.
Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ENVIRO-CLEAN

No additional information available

SODIUM METASILICATE 6834-92-0

No additional information available

TETRASODIUM EDTA 64-02-8

No additional information available

SODIUM XYLENE SULFONATE 1300-72-7

No additional information available

ALCOHOLS, C6-C12, ETHOXYLATED 68439-45-2

No additional information available

BUTHOXYETHANOL 111-76-2

No additional information available

USA - ACGIH - Occupational Exposure Limits

| | |
|----------------------|--|
| Local name | 2-Butoxyethanol (EGBE) |
| ACGIH OEL TWA | 20 ppm |
| Remark (ACGIH) | TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI |
| Regulatory reference | ACGIH 2019 |

USA - OSHA - Occupational Exposure Limits

| | |
|--------------------------------|---------------------------------|
| Local name | 2-Butoxyethanol |
| OSHA PEL TWA | 240 mg/m ³ 50 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Colour | : pink |
| Odour | : characteristic |
| Odour threshold | : No data available |
| pH | : 13.1 |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability | : Not applicable. |
| Vapour pressure | : No data available |
| Relative vapour density at 20°C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

No additional information available

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : No data available
Acute toxicity (dermal) : No data available
Acute toxicity (inhalation) : No data available

| SODIUM METASILICATE (6834-92-0) | |
|---|---|
| LD50 oral rat | 1152 – 1349 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 7 day(s)) |
| LD50 dermal rat | > 5000 mg/kg bodyweight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s)) |
| ATE US (oral) | 1152 mg/kg bodyweight |
| TETRASODIUM EDTA (64-02-8) | |
| LD50 oral rat | > 2000 mg/kg (Rat, Oral) |
| SODIUM XYLENE SULFONATE (1300-72-7) | |
| LD50 oral rat | > 7000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s)) |
| ALCOHOLS, C6-C12, ETHOXYLATED (68439-45-2) | |
| LD50 oral rat | > 1000 mg/kg (Rat, Oral) |
| LD50 dermal rabbit | > 2000 mg/kg (Rabbit, Dermal) |
| ATE US (oral) | 500 mg/kg bodyweight |

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| BUTHOXYETHANOL (111-76-2) | |
|----------------------------------|---|
| LD50 oral rat | 1746 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s)) |
| LC50 Inhalation - Rat | > 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s)) |
| ATE US (oral) | 1414 mg/kg bodyweight |
| ATE US (dermal) | 1100 mg/kg bodyweight |
| ATE US (gases) | 4500 ppmv/4h |
| ATE US (vapours) | 3 mg/l/4h |
| ATE US (dust,mist) | 1.5 mg/l/4h |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Causes severe skin burns. pH: 13.1 |
| Serious eye damage/irritation | : Causes serious eye damage. pH: 13.1 |
| Respiratory or skin sensitisation | : No data available |
| Germ cell mutagenicity | : No data available |
| Carcinogenicity | : No data available |

| BUTHOXYETHANOL (111-76-2) | |
|----------------------------------|----------------------|
| IARC group | 3 - Not classifiable |
| Reproductive toxicity | : No data available |
| STOT-single exposure | : No data available |

| SODIUM METASILICATE (6834-92-0) | |
|--|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |

| BUTHOXYETHANOL (111-76-2) | |
|----------------------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
| STOT-repeated exposure | : No data available |

| SODIUM METASILICATE (6834-92-0) | |
|--|---|
| NOAEL (oral, rat, 90 days) | 227 – 237 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |

| BUTHOXYETHANOL (111-76-2) | |
|-------------------------------------|---|
| NOAEL (dermal, rat/rabbit, 90 days) | > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |

| | |
|-------------------------------------|---------------------------------|
| Aspiration hazard | : No data available |
| Viscosity, kinematic | : No data available |
| Symptoms/effects after inhalation | : None under normal conditions. |
| Symptoms/effects after skin contact | : Burns. |
| Symptoms/effects after eye contact | : Serious damage to eyes. |
| Symptoms/effects after ingestion | : Burns. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

| SODIUM METASILICATE 6834-92-0 | |
|--------------------------------------|---|
| LC50 - Fish [1] | 210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value) |

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| SODIUM METASILICATE6834-92-0 | |
|---|--|
| EC50 - Crustacea [1] | 1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |
| TETRASODIUM EDTA64-02-8 | |
| LC50 - Fish [1] | 121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water) |
| EC50 - Crustacea [1] | 625 mg/l (24 h, Daphnia magna, Literature study) |
| SODIUM XYLENE SULFONATE1300-72-7 | |
| LC50 - Fish [1] | > 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value) |
| EC50 - Crustacea [1] | > 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| BUTHOXYETHANOL111-76-2 | |
| LC50 - Fish [1] | 1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal) |
| EC50 - Crustacea [1] | 1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 algae | 1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration) |
| NOEC (chronic) | 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | > 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d' |

12.2. Persistence and degradability

| SODIUM METASILICATE6834-92-0 | |
|--|---|
| Persistence and degradability | Biodegradability: not applicable. |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |
| ThOD | Not applicable (inorganic) |
| TETRASODIUM EDTA64-02-8 | |
| Persistence and degradability | Not readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | < 0.002 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 0.54 – 0.58 g O ₂ /g substance |
| SODIUM XYLENE SULFONATE1300-72-7 | |
| Persistence and degradability | Readily biodegradable in water. |
| ALCOHOLS, C6-C12, ETHOXYLATED68439-45-2 | |
| Persistence and degradability | Readily biodegradable in water. |
| BUTHOXYETHANOL111-76-2 | |
| Persistence and degradability | Readily biodegradable in water. |

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.3. Bioaccumulative potential

SODIUM METASILICATE6834-92-0

| | |
|---------------------------|----------------------------------|
| Bioaccumulative potential | Bioaccumulation: not applicable. |
|---------------------------|----------------------------------|

TETRASODIUM EDTA64-02-8

| | |
|---|----------------------|
| Partition coefficient n-octanol/water (Log Pow) | -2.6 |
| Bioaccumulative potential | Not bioaccumulative. |

SODIUM XYLENE SULFONATE1300-72-7

| | |
|---|---|
| Partition coefficient n-octanol/water (Log Pow) | -3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C) |
| Bioaccumulative potential | Not bioaccumulative. |

ALCOHOLS, C6-C12, ETHOXYLATED68439-45-2

| | |
|---|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 3.01 (Estimated value) |
| Bioaccumulative potential | Not bioaccumulative. |

BUTHOXYETHANOL111-76-2

| | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 0.81 (Experimental value, BASF test, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

12.4. Mobility in soil

SODIUM METASILICATE6834-92-0

| | |
|-----------------|---|
| Surface tension | No data available in the literature |
| Ecology - soil | No (test)data on mobility of the substance available. |

SODIUM XYLENE SULFONATE1300-72-7

| | |
|-----------------|---|
| Surface tension | 71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension) |
| Ecology - soil | No (test)data on mobility of the substance available. |

BUTHOXYETHANOL111-76-2

| | |
|--|--|
| Surface tension | 65.03 mN/m (20 °C, 2 g/l) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

| | |
|--|---|
| Regional waste regulation | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations. |
| Additional information | : Do not re-use empty containers. |

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 14: Transport information

14.1. UN number

UN-No. (DOT) : UN1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8

Hazard labels (DOT) : 8



14.4. Packing group

Packing group (DOT) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No. (DOT) : UN1760

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

ENVIRO-CLEAN

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information


according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 9/9/2025

Full text of hazard classes and H-statements

| | |
|------|---|
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating
Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection : C - Safety glasses, Gloves, Synthetic apron

Safety Data Sheet (SDS), USA 2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.