



WOMA[®] RENTAL UNITS

ECOMASTER ZWG

Powerful, versatile and efficient in every situation.

The EcoMaster ZWG is controlled by an integrated intermediate gearbox in a power range from 50 to 500 kW. This means that the entire range of high-pressure applications in industry can be covered and at the same time fuel consumption can be optimised for each field of application.



Technical Data EcoMaster ZWG

Unit type	EcoMaster D 700Z 1000/261 ZWG
Max. pressure bar	1.000
Max. volume flow in l/min	261
Fuel tank in l	900
Water tank in l	800
Weight in kg (inkl. LKW)	ca. 23.000
Measures in mm (L x W x H)	9.700 x 2.550 x 4.000
Standard accessories included	<ul style="list-style-type: none"> • High-pressure gun up to 1,500 bar • 50 m control line • 40 m high-pressure hose • 20 m inlet hose • Round jet nozzle • Protective clothing • Filter inserts (quantity depending on rental period)

ECOMASTER MK3/MK4

The mobile power pack.

The EcoMaster MK3/MK4 is a compact, high-performance unit for the maintenance of large structures and industrial plants, but also for many other applications in the industry, in the maritime sector, in the construction industry as well as in municipal services. The ultra-high pressure water jet unit is designed as a mobile trailer with a diesel engine.



Technical Data EcoMaster MK3

Unit type	EcoMaster MK3/MK4
Max. pressure bar	2.800/3.000
Max. volume flow in l/min	25
Fuel tank in l	200
Water tank in l	150
Weight in kg	ca. 3.000/2.500
Measures in mm (L x W x H)	ca. 4.450 x 2.030 x 2.330 (MK3) ca. 4.503 x 2.240 x 2.000 (MK4)
Standard accessories included	<ul style="list-style-type: none"> • High-pressure gun up to 3,000 bar • 50 m control line • 40 m high-pressure hose • 20 m inlet hose • Round jet nozzle • Protective clothing • Filter inserts (quantity depending on rental period)

Other unit versions on request.

ECOMASTER D 250Z

Flexible use in industrial cleaning.

The EcoMaster D250Z is a mobile powerhouse and offers a solution for various areas of industrial cleaning. With a delivery volume of up to 96 l/min, the unit is suitable for pipe bundle and tank cleaning, as well as manual cleaning work with the high-pressure lance in single or multi-consumer operation.



Technical Data EcoMaster D 250Z

Unit type	EcoMaster D 250Z 1000/71	EcoMaster D 250Z 1000/96
Max. pressure bar	1.000	1.000
Max. volume flow in l/min	71	96
Fuel tank in l	200	315
Water tank in l	150	220
Weight in kg	ca. 3.000	ca. 3.500
Measures in mm (L x W x H)	ca. 4.450 x 2.030 x 2.330	ca. 4.670 x 2.030 x 2.330

Standard accessories included

- 2x High-pressure gun up to 1,500 bar
- 2x 50 m control line
- 2x 40 m high-pressure hose
- 1x 20 m inlet hose
- 2x round jet nozzle
- 2x Protective clothing
- Filter inserts (quantity depending on rental period)

Ask us about our wide range of available water tools for your application.

ECOTHERM

Effective cleaning with hot water.

The hot water cleaner EcoTherm reaches performance levels, which otherwise are only achieved by bigger high-pressure units. This is because cleaning with hot water is more efficient and effective than with cold water, especially in the environment of oily contamination. For comparable cleaning tasks, a much lower operating pressure is usually sufficient.



Technical Data EcoTherm

Unit type	ET 600	ET 800
Max. pressure bar	600	800
Max. volume flow in l/min	40	32
Max. water temperature in C°	95	
Heating capacity in kW	2 x 90	
Heating oil tank in l	175	
Fuel tank in l	175	
Water tank in l	75	
Weight incl. operating material in kg	2.100	
Measures in mm (L x W x H)	4.150 x 1.950 x 2.330	

Standard accessories included

- High-pressure gun up to 1,500 bar
- 50 m control line
- 40 m high-pressure hose for hot water
- 20 m inlet hose
- Flat jet nozzle
- Protective clothing
- Filter inserts (quantity depending on rental period)



WHATEVER THE TASK. WE HAVE THE SOLUTION.

WOMA GmbH
Werthauer Straße 77-79
47226 Duisburg
T: +49 2065 304 0
F: +49 2065 304 200
rental@woma.karcher.com
www.woma-group.com



Follow us.