

## Fat Cap Graffiti Remover Brick, Masonry & Concrete Cleaner

SDS Number: H698027

Revision Date: June 27, 2017

Page 1 of 5

### 1 PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Fat Cap Graffiti Remover Brick, Masonry & Concrete Cleaner  
**Revision Date:** June 27, 2017  
**Version:** 44-77E  
**SDS Number:** H698027

**Manufactured for:** Canadian Contact:

**Kärcher North America**  
 4555 Airport Way  
 Denver, CO 80239  
 Phone: 303-738-2400  
 Email: info@karcherna.com

**Kärcher North America**  
 6535 Millcreek Drive, Unit 67  
 Mississauga, ON L5N 2M2  
 Phone: 905-672-8233

**Emergency Information:** INFOTRAC 1-800-535-5053 International 1-352-323-3500

### 2 HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**

- Physical, Flammable Liquids, 2
- Health, Acute toxicity, 4 Oral
- Health, Acute toxicity, 4 Dermal
- Health, Serious Eye Damage/Eye Irritation, 1

#### GHS Label Elements, Including Precautionary Statements

**GHS Signal Word:** **DANGER**

**GHS Hazard Pictograms:**



**GHS Hazard Statements:**

- H225 - Highly flammable liquid and vapour
- H302 - Harmful if swallowed
- H312 - Harmful in contact with skin
- H318 - Causes serious eye damage

**GHS Precautionary Statements:**

- P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 - Keep container tightly closed.
- P241 - Use explosion-proof electrical/ventilating/light/equipment.
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P264 - Wash thoroughly with soap and water after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P370+378 - In case of fire: Use ABC extinguisher for extinction.

## Fat Cap Graffiti Remover Brick, Masonry & Concrete Cleaner

SDS Number: H698027



Revision Date: June 27, 2017

Page 2 of 5

P403+235 - Store in a well ventilated place. Keep cool.

**Route of Entry:** Eyes, Skin, Inhalation:  
**Target Organs:** Eyes; Skin; Respiratory system;  
**Inhalation:** Can cause irritation and inflammation of the respiratory tract.  
**Skin Contact:** Irritating to skin; may cause burns, blisters and itching.  
**Eye Contact:** Irritating to eyes, eye damage may occur.  
**Ingestion:** Irritating to intestinal tract; may cause burns, vomiting, stomach pain, and disorientation.

**NFPA:** Health = 3, Fire = 4, Reactivity = 0, Specific Hazard = n/a  
**HMIS III:** Health = 3, Fire = 4, Physical Hazard = 0  
**HMIS PPE:** B - Safety Glasses, Gloves



### 3 COMPOSITION/INFORMATION OF INGREDIENTS

**Ingredients:**

Cas#	%	Chemical Name
64-17-5	31%	Ethanol
67-63-0	1%	Isopropanol
1310-58-3	27%	Potassium hydroxide
111-76-2	7%	Ethylene Glycol Butyl Ether

**OSHA Regulatory Status:**

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

### 4 FIRST AID MEASURES

**Inhalation:** Remove from exposure and get fresh air. Keep warm and at rest. Get medical attention immediately if artificial respiration is required.  
**Skin Contact:** Remove contaminated clothing, jewelry and shoes immediately. Flush affected area with large amounts of water, then use soap or mild detergent and large amounts of water for 15-20 minutes to cleanse area. If skin is severely irritated or burned, get medical attention immediately.  
**Eye Contact:** Immediately flush eyes with large amounts of water occasionally lifting upper and lower lids for at least 15 minutes. Get immediate medical attention.  
**Ingestion:** Rinse mouth with water. DO NOT INDUCE VOMITING unless instructed to by medical personnel. If vomiting occurs keep head lower than hips to help prevent aspiration. If person is unconscious, do not induce vomiting; turn their head to the side. Never make an unconscious person vomit or drink fluids. Get medical attention.

### 5 FIRE FIGHTING MEASURES



## Fat Cap Graffiti Remover Brick, Masonry & Concrete Cleaner

SDS Number: H698027

Revision Date: June 27, 2017

Page 3 of 5

**Flash Point:** 22.22° C / 72° F  
**Flash Point Method:** Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

### 6 ACCIDENTAL RELEASE MEASURES

Isolate area; keep unnecessary personnel away. Do not discharge into drains. Ventilate closed spaces before entering. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. Wear appropriate protective equipment and clothing during cleanup. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

### 7 HANDLING AND STORAGE

**Handling Precautions:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor. Keep container closed. Promptly clean up spills. Wash thoroughly after handling.  
**Storage Requirements:** Store out of reach of children; keep container closed; store in a cool, well-ventilated place.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Normal room ventilation is satisfactory for limited use.  
**Personal Protective Equipment:** HMIS PP, B | Safety glasses, Gloves

Ethanol 67-17-5 OSHA PEL 1000 ppm - 1900 mg/m3  
 Isopropanol 67-63-0 OSHA PEL 400 ppm/ 980 mg/m3

Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Clear yellow	<b>Odor:</b>	Alcohol
<b>Physical State:</b>	Liquid	<b>Solubility:</b>	Soluble
<b>Spec Grav./Density:</b>	8.74 lb/gallon		
<b>pH:</b>	12.8 @ 5% solution		

### 10 STABILITY AND REACTIVITY

**Chemical Stability:** Product is stable under normal conditions.  
**Conditions to Avoid:** None known  
**Materials to Avoid:** Strong oxidizing or acidic materials  
**Hazardous Decomposition:** Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.  
**Hazardous Polymerization:** Will not occur.

### 11 TOXICOLOGICAL INFORMATION

**Toxicity Data:**  
 Ethanol 64-17-5  
 Oral ( LD 50): 7060 mg/kg - Rat



## Fat Cap Graffiti Remover Brick, Masonry & Concrete Cleaner

SDS Number: H698027

Revision Date: June 27, 2017

Page 4 of 5

Inhalation ( LC 50): 20000 ppm/10H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

### Isopropanol 67-63-0

Oral ( LD 50): 5045 mg/kg - Rat

Inhalation ( LC 50): 16000 ppm/8H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

### Potassium hydroxide 1310-58-3

Oral ( LD 50): 273 mg/kg - Rat

Inhalation ( LC): Not listed on RTECS

Skin irritation: Severe - Human

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

## 12 ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

## 13 DISPOSAL CONSIDERATIONS

Recommendation: Consult with the disposal agency and the relevant authorities. Empty containers may be cleaned with water.

## 14 TRANSPORT INFORMATION

UN2920 Corrosive liquids, flammable, n.o.s., 8, (Potassium hydroxide, Ethanol), II  
Ship in accordance with 49 CFR parts 100-185.



## Fat Cap Graffiti Remover Brick, Masonry & Concrete Cleaner

SDS Number: H698027

Revision Date: June 27, 2017

Page 5 of 5

15

### REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Ethanol (64-17-5) [31%] MASS, OSHAWAC, PA, TSCA, TXAIR

Isopropanol (67-63-0) [1%] MASS, NJHS, NRC, OSHAWAC, PA, SARA313, TSCA, TXAIR, WHMIS

RQ(1000LBS), Potassium hydroxide (1310-58-3) [27%] CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

Ethylene Glycol Butyl Ether (111-76-2) [7%] MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

Regulatory CODE Descriptions

All components are listed on TSCA

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

MASS = MA Massachusetts Hazardous Substances List

NJHS = NJ Right-to-Know Hazardous Substances

NRC = Nationally Recognized Carcinogens

OSHA WAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

RQ = Reportable Quantity

SARA313 = SARA 313 Title III Toxic Chemicals

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

WHMIS = Workplace Haz Mat Info Sys Canada

16

### OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager