



ECOMASTER CLASSIC

Simply to use, simply robust, simply efficient.

The EcoMaster Classic is designed for the usage in rough conditions. It persuades with it's compact, robust and low-maintenance construction and simple operation. The high-pressure units are diverse, flexible and usable, even in extreme climates or difficult environmental conditions.

Advantages at a glance:

- All devices are fitted with robust, low maintenance and strong performance WOMA high-pressure pumps.
- The compact design with stable frame construction or crash frames enables easy usage in difficult areas.
- Equipped with crane hooks for easy transport, it is also optionally available as a trailer construction.
- The EcoMaster Classic aggregates are particularly suitable for heavy soiling and caking in the industry, as e.g. commonly found in heat exchangers, meshes, filters and pipes.
- The EcoMaster Classic offers the optimal equipment for the refurbishment and removal of concrete or coating, as well as for cleaning.
- The large supply tank also ensures a calm water cycle in areas with limited supply of fresh water.
- Low operational costs due to high service life, minimal maintenance costs and simple servicing.



- 1** The EcoMaster D 250M Classic, with an operational pressure of up to 3,000 bar, offers the necessary performance for the removal of concrete and coating.
- 2** The EcoMaster D 150Z Classic is ideal for cleaning the exterior of tanks and removing coatings.
- 3** With a volume flow of up to 72 l/min, the EcoMaster D 150Z Classic is the optimal system for internal tank cleaning combined with the WOMA TankMaster cleaning heads.

Technical Data

Unit type	EcoMaster D 250M Classic	EcoMaster D 250Z Classic	EcoMaster D 190Z Classic	EcoMaster D 150Z Classic	EcoMaster D 150Z Classic	EcoMaster D 250Z Classic
Max. pressure in bar	2,800	3,000	1,500	1,500	750	750
Max. volume flow in l/min	25	21	50	36	68	94
Weight in kg (incl. operating fluids)	2,500	2,500	2,500	2,500	2,500	2,500
Measures in mm (L x W x H)	2,880 x 1,510 x 1,820		2,880 x 1,510 x 1,820		2,880 x 1,510 x 1,820	

Unit type	EcoMaster D 250 Z Classic			EcoMaster D 250Z Classic
Max. pressure in bar	1,500	1,000	720	400
Max. volume flow in l/min	60	96	133	219
Weight in kg (incl. operating fluids)	3,425	3,425	3,425	3,425
Measures in mm (L x W x H)	3,200 x 1,720 x 2,200	3,200 x 1,720 x 2,200	3,200 x 1,720 x 2,200	3,200 x 1,720 x 2,200