

makes a difference









HIGH-PRESSURE TRAILERS

Independence and reliability on the road

BECOME INDEPENDENT



HD trailer

Our configurable high-pressure trailers combine extraordinary mobility and maximum user-friendliness with an innovative machine concept. Our HD and HDS trailers are the ideal solution for municipalities, construction sites, rental fleets and industry.



HDS trailer

HIGH-PRESSURE MOBILE CLEANING

A well-designed concept instead of spontaneous tinkering. Like us, they don't do things by halves. Our trailers are based on a well-designed integrated concept with defined properties and capabilities: uncompromising performance, high mobility, ease of use and maximum independence. We have prioritised the components from our tried-and-tested high-pressure cleaners and have used very few new ones. This means, in addition to the known benefits of the technology, we have been able to keep the work undertaken by our service staff and the spare parts logistics simple.

Our HD and HDS trailers make it possible to use powerful high-pressure technology on the move and even in locations without a power or water supply. Durability, reliability and efficiency also top the list of features for this concept.

Many components come from our high-pressure cleaner model series, which has been tried-and-tested a million times over. Operating the machine is very simple. The storage compartment in the rear for canisters, accessories and other items, completes the impressive ergonomics concept. Configuration options make the trailer your custom machine.







Ease of use: Operating the machine is just as simple and convenient as with all Kärcher HD/HDS trailers with EASY Operation. This oneswitch operation makes it extremely easy for the user to handle. At the same time, it reduces the risk of operating errors to the bare minimum.

- Hose reels reduce set-up times and provide safe storage.
- The roomy storage compartments boast plenty of space for accessories, tools, cleaning agents and everything else you might need for the cleaning task at hand.

Low maintenance: Every machine needs servicing on a regular basis. The large machine hood on the HDS trailer, under which all the important components are positioned within easy access, and the free access on the HD trailer, along with the use of tried-and-tested components, make work easier for our Kärcher service technicians.

 Well-designed service menu on the HDS trailer for rapid diagnostics.

do this.

 Customised service packages tailored precisely to your individual requirements.

Reliability: HD and HDS trailers are systematically designed for long service life in daily use. A large number of tried-and-tested Kärcher components, including burners, pumps and control electronics in particular, have been used to

Numerous safety functions protect against damage in the case of failure, for example the water shortage protection on the HDS trailer stops the pump from dry running. And the water softening feature protects the heating coil against harmful lime deposits.

All HD/HDS trailers have an antifreeze system to protect the machine in cold outside temperatures.

HD TRAILER: STAY COOL UNDER PRESSURE

High-pressure cleaning and Kärcher go hand in hand. We have been driving high-pressure cleaning forwards by means of innovations for several decades now. We are now making this technology more mobile than ever before.

Independence: Powerful and reliable Yanmar diesel and Honda petrol engines (all EU STAGE V) enable use without the need for a power supply. You always have everything you need for the cleaning application right there on the trailers: water, cleaning agents, accessories.

The large integrated water tank on the HD trailer allows for independent cleaning at full performance for up to one hour and, with a reduced water flow, for up to two hours. You can choose to add an additional 20-litre fuel canister to your HD trailer. which will enable long periods of use.

Efficiency: An HD trailer shows initiative.

If the high-pressure gun is not actuated, automatic speed reduction lowers the noise level and fuel consumption. Individuality: You can configure your HD trailer to match your individual requirements. That also includes being able to opt for a forklift-compatible platform instead of a trailer.

The purpose of use and existing vehicle fleet will decide whether your HD module comes with or without an axle. As an alternative to the trailer, you can choose the Cab platform version which you can use on loading platforms or in a static position on site. The maximum support load of 75 kg gives you independence and flexibility. You can tow the HD trailer with virtually any passenger vehicle.





HDS TRAILER: THINGS ARE HOTTING UP

There are cleaning applications for which cold water under high pressure does not achieve the required results. Or at least, not in a reasonable period of time. That's where our hot water high-pressure cleaners come into play. Use them to remove graffiti, chewing gum, oils and greases quickly and easily.

Independence: powerful and reliable Yanmar diesel engines (EU STAGE V) enable use without the need for a power supply. You always have everything you need for the cleaning application right there on the HDS trailers: water, cleaning agents, accessories.

The large integrated water tank on the HDS trailer allows for independent cleaning at full performance for up to 30 minutes and, with a reduced water flow, for up to one hour. The large fuel tank means you can perform long cleaning applications without interruption.

Individuality: you can configure your HDS trailer to match your individual requirements. That also includes being able to opt for a forklift-compatible platform instead of a trailer. The purpose of use and existing vehicle fleet will decide whether your HDS module comes with or without an axle.

As an alternative to the trailer, you can choose the Skid or Cab platform versions which you can use on loading platforms or in a static position on site. Hose reels for the water connection and the high-pressure hose reduce the set-up times and provide safe storage.

Efficiency: The combination of effective Kärcher burners, powerful heat exchangers and eco!efficiency mode results in noticeable savings in fuel and reduces emissions to a minimum. An HDS trailer switches itself off no later than after a standby time of 45 minutes to save fuel. If the high-pressure gun is not actuated, automatic speed reduction lowers the noise level and fuel consumption.

- Heat exchangers that preheat the water using waste heat from the engine use up to 14 per cent less fuel.
- In Kärcher ecolefficiency mode, the water temperature is limited to 60°C, which is more than sufficient for most applications and noticeably reduces consumption.





HD/HDS TRAILERS IN USE

A coherent concept always takes into account all the important aspects: the tasks, operation, attachment and removal, efficiency and environmental protection.



Our trailers are highly mobile thanks to short set-up times, extremely convenient due to electro start and ease of operation, and their large water tank and hose reel make them self-sufficient and flexible. With our trailers, you can access any location of use with ease and can even clean without a power or water supply. Fuel-efficient, clean engines in line with EU STAGE V ensure superior performance with minimum consumption and emissions.










TYPICAL CLEANING TASKS IN MUNICIPALITIES

- Cleaning of public areas: street furniture, rubbish bins, open spaces, play equipment
- Cleaning of road infrastructure: roads, tunnels, traffic lights and signs
- **Cleaning of car parks:** barriers, floors and walls
- Cleaning of buildings in outside areas: walls, doors, roofs and portals
- **Special cleaning:** removal of graffiti and chewing gum without a trace

TYPICAL CLEANING TASKS ON CONSTRUCTION SITES

- Facade cleaning and renovation: soot, grease, bird droppings
- Cleaning of construction vehicles and equipment: scaffolding, concrete covers and planking
- Restoration of monuments
- Building refurbishment after fires















Technical data		HD 9/23 De	HD 9/23 Ge
Engine manufacturer		Yanmar	Honda
Engine type		L100 V/Diesel	GX 390/Petrol
Engine rating	kw / PS	7.4 / 10	9.5 / 13
Flow rate	I/h	400-930	400-930
Working pressure	bar / MPa	40-230 / 4-23	40-230 / 4-23
Max. inlet temperature	°C	60	60
Unladen weight	kg	600	600
Dimensions	mm	3,560 × 1,496 × 1,484	3,560 × 1,496 × 1,484
Fuel consumption, full load	l/h	1.9	3.5
Order no.		1.524-954.2	1.524-954.2

Spray gun		EASY!Force Advanced	EASY!Force Advanced
High-pressure hose m		Standard: 15/Premium: 30	Standard: 15/Premium: 30
Spray lance	mm	1,050	1,050
Servo Control			
Power nozzle			
Dirt blaster		Premium	Premium


■ Included in the scope of supply.

Options (ex works)

- High-pressure hose reel
- Tarpaulin for the rear
- Protective guard and splashback for the front
- 20-litre diesel canister with transport lock
- Elapsed time counter
- Crane hook (trailer only)
- Shock absorber (trailer only)
 Impact protection for water tank (trailer only)
- Flashing beacon (trailer only)

- High-pressure hose reel
- Tarpaulin for the rear
- Protective guard and splashback for the front
- 20-litre petrol canister with transport lock
- Elapsed time counter
- Crane hook (trailer only)
- Shock absorber (trailer only)
 Impact protection for water tank (trailer only)
- Flashing beacon (trailer only)

- On stationary frame with forklift pockets
- Integrated 1,000-litre water tank
- On chassis, support load of 75 kg
- Integrated 1,000-litre water tank
- With optional shock absorber
- With optional crane hook
- With optional impact protection for water tank
 With optional flashing beacon

















- Speed reduction
- Speed control
- With optional automatic pressure relief
- Speed reduction
- Speed control • With optional automatic pressure relief
- Speed reduction
- Cleaning agent dosing unit
- Servo Control
- With optional preparation for two-spray lance operation
- Speed reduction
- Cleaning agent dosing unit
- Servo Control

Technical data					
Engine manufacturer		Yanmar	Yanmar	Yanmar	Yanmar
Fuel		Diesel	Diesel	Diesel	Diesel
Engine rating	kW	19	19	19	19
Flow rate	l/h	500-900	650-1,300	900-1,700	900-1,300
Working pressure	bar / MPa	150-500 / 15-50	100-350 / 10-35	70-200 / 7-20	50-200 / 5-20
Max. temperature	°C	85 / 98	85 / 98	80 / 98	85 / 98
Unladen weight	kg	950	950	950	950
Dimensions	mm	3,646 × 1,747 × 1,735	3,646 × 1,747 × 1,735	3,646 × 1,747 × 1,735	3,646 × 1,747 × 1,735
Diesel consumption, full load	kg/h	9.7	12.4	11.8	11.3
Diesel consumption,	kg/h	7.5	9.3	9.7	8.2
eco!efficiency mode					
Order no.		1.524-521.2	1.524-521.2	1.524-952.2	1.524-952.2

Accessories package (optional)					
Spray gun		Industrial trigger gun	Industrial trigger gun	EASY!Force Advanced	EASY!Force Advanced
High-pressure hose	m	30	30	30	30
Spray lance	mm	700	700	1,050	1,050
Power nozzle					•
Servo Control		-	-		•
Pressure adjustment via speed regulation					

■ Included in the scope of supply. □ Optional.

Mobility

- Stationary frame with forklift pockets
- Without water tank Without covers
- Stationary frame with forklift pockets
- Integrated 500-litre
- water tank ■ With covers

- On chassis
- Integrated 500-litre water tank
- With covers
- With optional shock absorbers

15

Please contact us for more information:

Head Office Germany

Alfred Kärcher SE & Co. KG Alfred-Kärcher-Straße 28–40 71364 Winnenden

Phone +49 7195-14-0 Fax +49 7195-14-2212

www.kaercher.com

North America

Kärcher North America 4555 Airport Way Denver, CO 80239

Phone +1 303-738-5805 Fax +1 303-865-2758

www.karcherna.com

United Kingdom

Kärcher (UK) Ltd Kärcher House Brookhill Way Banbury Oxon OX16 3ED

Phone +44 1295-752-000 Fax +44 1295-752-103

www.karcher.co.uk

Ireland

Kärcher Ltd Unit 4 E.P. Mooney Business Park Walkinstown Avenue Dublin 12

Phone +353 1-409-7777 Fax +353 1-409-7775

www.karcher.ie

South East Asia

Regional Head Office South East Asia

Karcher South East Asia Pte Ltd 3 Depot Close #05-01 Singapore 109840

Phone +65 6897-1811 Fax +65 6897-1611

www.karcher.com.sg

Hong Kong

Kärcher Limited Unit 01, 22/F, Westley Square 48 Hoi Yuen Road Kwun Tong, Kowloon

Phone +852 2-357-5863 Fax +852 2-357-5632

www.karcher.com.hk

Australia

Karcher Pty Ltd 385 Ferntree Gully Road Mount Waverley Victoria, AU 3149

Phone 1800 675-714 (Free Call)

www.karcher.com.au

New Zealand

Karcher Ltd 66 Allens Road East Tamaki Auckland 2013

Phone +64 9-274-4603 Fax +64 9-274-6932

www.karcher.co.nz

North Africa

Kärcher SARL Immeuble Yasmine Tower Bloc A 6ème étage, bureau A 6.6 Centre Urbain Nord 1082 Tunis Tunisia

Phone +216 36339020

info@tn.kaercher.com www.kaercher.tn

East Africa

Karcher Limited Regus Fortis Office Park P. O. Box 66488-00800 Block C, Ground floor Muthangari Drive Westlands Nairobi Kenya

Phone +254 205148145

info@ke.kaercher.com www.kaercher.com/ke

South Africa

Kärcher (Pty) Ltd Cnr Mount Joy & George Allen Rd Wilbart Ext. 2 PO Box 11818 Vorna Valley, 1686

Phone +27 11-657-7300 Fax +27 11-657-7440

www.karcher.co.za

Middle East

Karcher FZE Quality Cleaning Systems Jebel Ali Free Zone Plot No. S-10104 South Zone RA 08, XB 1, Jebel Ali Dubai

Phone +971 4-886-1177 Fax +971 4-886-1575

customercare@ae.kaercher.com www.karcher.ae

Qatar

Karcher LLC Office No 133, Regus Building D Ring Road PO Box 35176

Phone +974 4-423-1319

customercare@ae.kaercher.com www.kaercher.ae

Caribbean

Karcher S.R.L. Calle 5ta, esq. Calle 18, Nave 1 Villa Aura Santo Domingo Oeste Dominican Republic

Phone +1 809-379-3700 Fax +1 809-379-3777

info@do.kaercher.com www.kaercher.com/do